PUBLIC ABSTRACT

Applicant (primary) name: Southern Company Services, Inc.

Applicant's address: 600 North 18 th Street Birmingham AL 35291

Street City State Zipcode

Team Members (if any): (listing represents only participants

at time of application, not necessarily final team membership)

Southern Co. Svcs. Birmingham AL 35291

Name City State Zipcode

Peabody Energy St. Louis MO 63101 Name City State Zipcode

Kellogg Brown and Root Houston TX 77002

Name City State Zipcode (Use continuation sheet if needed.)

Proposal Title: 300-MW Demonstration of Coal Gasification Power

Generation, Incorporating an Air-Blown KBR Transport

Gasifier

Commercial Application: X New Facilities X Existing Facilities

_ Other, Specify:

Technology Type: Conversion (Gasification)

Estimated total cost of project: (May not represent final negotiated costs.)

Total Estimated Cost: \$ 719,506,512 Estimated DOE Share: \$ 250,000,000 Estimated Private Share: \$469,506,512

PUBLIC ABSTRACT (cont'd)

Anticipated Project Site(s): Greene County AL 36732

Location (city, county, etc.) State Zipcode

McKinley County NM 87020 Location (city, county, etc.) State Zipcode

McKinley County NM 87013 Location (city, county, etc.) State Zipcode

Randolph County IL 62286 Location (city, county, etc.) State Zipcode

Warrick County IN 47619 Location (city, county, etc.) State Zipcode

Type of coal to be used: U.S. PRB (sub-bituminous) U.S. Bituminous

Primary Alternate (if any)

Size or scale of project: 3322

Tons of coal/day input

And/or

297 MW Megawatts, Barrels per day, etc.

Other (if necessary)

Duration of proposed project: 112 (From date of award) (Months)

PRIMARY CONTACT:

For additional information, Randall Rush

interested parties should contact: Name

Director – Power Systems Development Facility

Position

Telephone Number Southern Company Services, Inc.

Company

rerush@southernco.com P.O. Box 1069

e-mail address Address

Wilsonville AL 35186

City State Zipcode

Alternative Contact: Tim Pinkston

Name

Tech. Mgr. – Power Systems Development

Facility Position

(205)670-5860

(205)670-5842

Telephone Number Southern Company Services, Inc.

Company

tepinkst@southernco.com P.O. Box 1069

e-mail address Address

Wilsonville AL 35186

City State Zipcode

PUBLIC ABSTRACT (cont'd)

Brief description of project:

Demonstration of an air-blown transport reactor integrated gasification (TRIGTM) combined cycle power plant is proposed. The transport reactor design is based on Kellogg Brown and Root's fluidized catalytic cracker technology used successfully for over 50 years in the petroleum refining industry to produce gasoline from middle distillates.

The demonstration unit will generate 297 MW (net) at 44.4 percent efficiency (LHV), a heat rate of 7,680 Btu/kWh. It will be the cleanest, and when adjusted for local conditions, most efficient coal-fired power plant technology in the world. The demonstration unit design involves a single gasifier/gas turbine train and one steam turbine. This configuration is sometimes referred to as 1-on-1. Following demonstration at this size, scale up to a more economical 600 MW 2-on-1 configuration can be achieved at no risk since only the steam turbine will increase in size.

The gasifier is fed with nominally 140 tons/hr of sub-bituminous coal and 4 tons/hr of limestone for in-situ sulfur capture. Syngas with a nominal heating value of 110 Btu/SCF is fired in a General Electric 7FA turbine generating 197 MW. The gas turbine flue gas discharges into a single pressure, heat recovery steam generator (HRSG). High-pressure saturated steam raised in the HRSG is mixed with steam from a syngas cooler, superheated in the HRSG and expanded through a reheat steam turbine operating at 1,815 psia/1,000°F/1,000°F. The steam turbine output is 118 MW.

Within the HRSG, a unit for selective catalytic reduction (SCR) of Nox is installed after the evaporator circuit where the flue gas is in the optimal temperature range of 600 to 700°F. After the HRSG, the flue gas passes through a flue gas treatment (FGT) unit that incorporates a proprietary Southern Company modification that lowers emissions. This FGT unit removes almost all the environmental species of interest, including sulfur dioxide and trioxide, hydrogen chloride, hydrogen fluoride, ammonia slip from the SCR unit, oxidized and unoxidized mercury, trace elements, and volatile organic compounds. Char and ash are removed from the gasifier island, water is added for dust suppression, and the mixture is disposed of in a landfill that is designed to collect and recycle rainfall for use in the demonstration unit. Tests show that the char and ash from the gasifier are non-hazardous.